

PRODUCT DATA SHEET EWO® Wellwater-Optimizer BWO



APPLICATION

The use of the EWO® Wellwater-Optimizer helps to improve the quality of standing and slowly flowing waters.
The self-cleaning power of the water is supported.
A continuous and permanent function is given.

FUNCTIONALITY

The EWO® BWO works with the **2 mechanisms of the EWO® water optimization:**
+ information transfer
+ magnetism

PRE-CONDITIONS FOR INSTALLATION

Local installation regulations, general guidelines and technical data must be noted.

The installation location must be frost-proof and ensure protection against chemicals, dyes, solvents, vapors and environmental influences.

AREAS OF APPLICATION

The EWO® BWO can be used in drinking- and raw water:

- Wells (at least 50cm diameter)
- Ponds & biotopes
- Pools (in the expansion tank)
- Spring water collection bassin
- Rainwater tanks
- Slurry pits

MOUNTING INSTRUCTIONS

Attach the EWO® Wellwater-Optimizer with a nylon rope in the lower third.

At slurry pits:

Attach the EWO® Wellwater-Optimizer with a nylon rope in the upper third using a float.

TECHNICAL DATA



OPERATIONS AND MAINTENANCE

The EWO® BWO is maintenance free.

SCOPE OF DELIVERY

1 EWO® BWO (single- or double cylinder)

WARRANTY

The latest version of the national statutory warranty provisions apply

Contact:

Name: EWO Wassertechnik GmbH
Street: Anzing 48
ZIP-Code: 4113
City: St. Martin/Mühlkreis
State: Austria
Tel: +43 7232 2754-0
E-Mail: office@ewo-wasser.at

The information corresponds to the knowledge available at the time of preparation. Printing errors, mistakes and changes are reserved. Illustrations are not to scale. All information is based on the characteristics of the Austrian market.
Edition: January 2021